

## Model 5100 Portable Gas Analyzer

For the Measurement of Moisture in Bulk Gas and Hydrocarbon Streams  
Based on Tunable Diode Laser Absorption Spectroscopy (TDLAS)

### SYSTEM OVERVIEW

The AMETEK Model 5100 Portable Gas Analyzer is used for spot checking the performance of plant equipment, like dryers, and verifying the measurements of on-line moisture analyzers. The portable unit operates on the principle of TDLAS and guarantees high specificity, sensitivity and fast response speeds. The unit includes a reference cell for laser line-lock. This feature eliminates measurement errors due to the laser wavelength shifting with the ambient temperature variations. Gas sampling accessories are offered with the Model 5100 Portable Gas Analyzer to make the unit a customizable solution. It is factory calibrated and the calibration is NIST traceable.



### FEATURES & BENEFITS

- ▶ Noncontact measurement guarantees low maintenance
- ▶ Battery powered and provides up to 8 hours of use before requiring a charge
- ▶ Application specific gas cells with a wide range of pathlengths available
- ▶ Excellent wavelength stability
- ▶ Reference cell for laser line-lock
- ▶ Membrane keypad for inputting parameters and selecting displays
- ▶ Superior built-in diagnostics
- ▶ Alphanumeric LCD backlit display of 4 lines, each with 20 characters
- ▶ USB 2.0 compatible user interface for PC communications
- ▶ Advanced digital signal processing

# Model 5100 Portable Gas Analyzer

## SPECIFICATIONS

**Range:** 250 ppmv to 2500 ppmv for natural gas. Other ranges depend on the application. Contact AMETEK for more information.

**Accuracy:** Typically  $\pm 2\%$  of range

**Sample Cell pressure:** Ambient atmospheric

**Speed of response:** 90% in less than 15 seconds. Less than 1 second for individual photometric measurements.

**Battery Life:** Approximately 8 hours under normal use

**Ambient temperature:** -20 °C to 50 °C (also nominal storage temperature range)

**Physical dimensions (W x H x D):** 15 cm x 25 cm x 8 cm  
(5.9 in. x 9.8 in. x 3.1 in.)

**Weight:** 5 kg (11 lbs.)

**Compliance (pending):**

North American Class I, Div 2, Groups B, C, & D T3

CE (EMC, Low Voltage)

Ex n IIB+H2 T3

TDLAS



150 Freeport Road, Pittsburgh, PA 15238  
Ph. +1-412-828-9040, Fax +1-422-826-0399  
www.ametekpi.com



© 2011, by AMETEK, Inc.  
All rights reserved. Printed in the U.S.A.  
F-0248 Rev. 3 (0411)

*One of a family of innovative process analyzer solutions from AMETEK Process Instruments.  
Specifications subject to change without notice.*

**SALES AND MANUFACTURING:**

**USA - Delaware**  
455 Corporate Blvd., Newark DE 19702 • Tel: +1-302-456-4400, Fax: +1-302-456-4444

**USA - Oklahoma**  
2001 N. Indianwood Ave., Broken Arrow OK 74012 • Tel: +1-918-250-7200, Fax: +1-918-459-0165

**CANADA - Alberta**  
2876 Sunridge Way N.E., Calgary, AB T1Y 7H9 • Tel: +1-403-235-8400, Fax: +1-403-248-3550

**WORLDWIDE SALES AND SERVICE LOCATIONS:**

**USA - Texas**  
Tel: +1-713-466-4900, Fax: +1-713-849-1924

**CHINA**  
Beijing / Tel: 86 10 8526 2111, Fax: 86 10 8526 2141  
Chengdu / Tel: 86 28 8675 8111, Fax: 86 28 8675 8141  
Guangzhou / Tel: 86 20 8363 4768, Fax: 86 20 8363 3701  
Shanghai / Tel: 86 21 5868 5111, Fax: 86 21 5866 0969

**FRANCE**  
Tel: 33 1 30 68 89 20, Fax: 33 1 30 68 89 29

**GERMANY**  
Tel: 49 21 59 91 36 0, Fax: 49 21 59 91 3639

**INDIA**  
Tel: 91 80 6782 3200, Fax: 91 80 6782 3232

**SINGAPORE**  
Tel: 65 6484 2388, Fax: 65 6481 6588