

## Model 5830 Moisture Analyzer

### Features

- ▶ Quartz-crystal technology provides accuracy, speed, and calibration stability
- ▶ On-line verification system confirms analytical performance
- ▶ Intuitive, easy-to-use interface with keypad and display allows quick access to operating variables
- ▶ Multi-gas compatibility makes the analyzer ideal for periodic testing of multiple sample gases
- ▶ Menu-driven gas selection eliminates all manual adjustments

Building upon the success of our quartz-crystal moisture measurement technology, AMETEK's Model 5830 is an easy-to-use process moisture analyzer that offers a truly remarkable combination of performance features: exceptional accuracy, multi-gas compatibility, fast response speed, and wide measurement range.

The 5830 is ideal for critical moisture measurement applications including high purity gas production, semi-conductor gases, and industrial gas production and quality assurance. Equipped with an on-line verification system, this state-of-the-art analyzer is designed to rapidly build and maintain operator confidence in its analyses. The verification system allows you to challenge the analyzer's sensor at will with either a zero gas or an actual NIST-traceable moisture concentration to check both its baseline stability and responsiveness to real moisture. No other manufacturer offers these exclusive abilities in their moisture analyzers.

### Superior Performance

#### **Multi-gas compatibility**

The Model 5830 combines the excellent multi-gas compatibility of the Model 5800 with a new, easy-to-use operator interface. It is completely compatible with virtually all non-corrosive gases including inerts (He, Ar, Ne, Xe, Kr), H<sub>2</sub>, O<sub>2</sub>, N<sub>2</sub>, air, and many specialty gases such as sulfur hexafluoride. A single, simple menu selection is all that is needed to re-configure the 5830 for a new gas type. There are no other necessary adjustments on the analyzer.

So, if you want to analyze industrial, high purity, or semiconductor grade gases, and need an instrument that is compatible with a wide range of gases, turn to the Model 5830.

#### **Exceptional accuracy**

The Model 5830 is perfect for moisture applications that require accurate results. The accuracy of this analyzer,  $\pm 20$  ppbv or  $\pm 10\%$  of reading, is exceptional when you consider that a new aluminum oxide sensor is typically specified with an accuracy of  $+72\%/-57\%$  of reading (converted from the dew point specifications) for a moisture concentration of 0.1 ppmv at 14.7 psia.

Quartz-crystal technology and an on-line verification system combine to constantly provide assurance that the analyzer is continuing to provide you with this superior level of performance.

#### **On-line verification system confirms analytical performance**

The on-line verification system in the 5830 uses internal zero and internal moisture verification systems. The zero verification system strips the moisture from the sample gas prior to analysis by the sensor. This allows you to verify the zero point of the sensor's calibration, enhancing accuracy and confidence in ppbv measurements. The moisture verification system employs a NIST-traceable moisture generator to allow you to quickly confirm the sensor's responsiveness and accuracy at any time on your sample gas. The generator adds a known amount of moisture to conditioned gas. The resulting known wet gas is then directed to the analyzer's sensor, verifying proper sensor and system operation. An alarm contact alerts the operator if the analyzer fails verification. The verification sequences may be started on programmable schedule or on manual demand.



## Fast response speed

The Model 5830 responds quickly to both increases and decreases in moisture concentration because the analyzer employs a unique non-equilibrium measurement technique. This technique continuously exposes the sensor to "wet" sample gas followed by "dry" sample gas to make its analysis. With this technique, the analyzer never needs to wait for the sensor to reach equilibrium to establish its accurate measurement. Importantly, this technique is based upon the defined, repeatable physical properties of moisture transport to/from the sensor's surface. This means that quartz-crystal technology never employs the questionable prediction software often used to "speed-up" other, more limited technologies.

AMETEK's unique technique makes possible accurate moisture readings far faster than would be possible under equilibrium, or continuous "wet" sample gas, operating conditions.

## Wide measurement range

The Model 5830 accurately measures from 0.02 ppmv (20 ppbv) to 100 ppmv. While the recommended usable range is between 0.02 ppmv and 100 ppmv, the analyzer will provide measurements up to 1000 ppmv so that you can capture the nature of a process upset.

## Performance Specifications

**Compatible Gases:** Inerts (He, Ar, Ne, Xe, Kr), H<sub>2</sub>, O<sub>2</sub>, N<sub>2</sub>, air, and some specialty gases such as sulfur hexafluoride. CO<sub>2</sub> requires a custom measurement cell. (Contact the factory to confirm compatibility with other gases.)

**Range:** 0 to 100 ppmv. Indicates trend to 1000 ppmv. Display is software settable to show ppmv, ppbv, or dew point (requires pressure input).

**Reference Dryer Life:** Over 1,000,000 ppmv-hrs nominal (eg. Dryer will last over five years with a 20 ppmv inlet moisture concentration.)

**Limit of Detection:** 20 ppb

**Accuracy:** ±20 ppbv or ±10% of the reading, whichever is greater

**Response Time:** 63% of a step change in either direction in less than 5 minutes

**Inlet Pressure:** 138 to 345 kPa (20 to 50 psig)

**Exhaust Pressure:** Atmospheric

**Sample Flow Requirements:** Approx. 150 sccm in sample saver mode. Approx. 1 slpm with by-pass open.

**Sample Gas Temperature:** 0° to 100°C (32° to 212°F)

### Outputs

Four-line digital display

A fully programmable 4 to 20 mA analog output

RS485/RS232 serial communication

**Alarms:** Three dry contact closures, 32 VDC maximum, 1 A non-inductive load (moisture, data valid, and system alarm). Alarm signals are available on the RS485 interface.

**Software Features:** Displays ppmv or ppbv moisture reading or dew point, timer status, and instrument status

**Environmental Conditions:** 5° to 50°C (41° to 122°F), 90 percent relative humidity, noncondensing, noncorrosive atmosphere. Optimal performance in ppbv applications is achieved when the ambient temperature is maintained within ±2°C.

### Utility Requirements

85 to 265 volts, 47 to 63 Hz, 185 W

Instrument Air: 483 to 690 kPa (70 to 100 psi)

**Mounting Configuration:** 19-inch rack/bench-top installation

**Dimensions:** (W x H x D): 48.3 x 13.3 x 41.9 cm (19 x 5.25 x 16.5 in.)

**Net Weight:** 12.7 kg (28 lbs.)

### Approvals and Certifications

CE

MET Certified to:

UL/CSA General Safety Requirements

NEC/CEC Class I, Division 2, Groups A, B, C, D T4



455 Corporate Blvd., Newark, DE 19702  
Ph. +1-302-456-4400, Fax +1-302-456-4444  
www.ametekpi.com



© 2011, by AMETEK, Inc.  
All rights reserved. Printed in the U.S.A.  
F-0142 Rev 3 (0311)

One of a family of innovative process analyzer solutions from AMETEK Process Instruments.  
Specifications subject to change without notice.

### SALES AND MANUFACTURING:

**USA - Oklahoma**  
2001 N. Indianwood Ave., Broken Arrow OK 74012 • Tel: +1-918-250-7200, Fax: +1-918-459-0165

**USA - Pennsylvania**  
150 Freepoint Road, Pittsburgh PA 15238 • Tel: +1-412-828-9040, Fax: +1-412-826-0399

**CANADA - Alberta**  
2876 Sunridge Way N.E., Calgary, AB T1Y 7H9 • Tel: +1-403-235-8400, Fax: +1-403-248-3550

### WORLDWIDE SALES AND SERVICE LOCATIONS:

**USA - Texas**  
Tel: +1-713-466-4900, Fax: +1-713-849-1924

**CHINA**  
Beijing / Tel: 86 10 8526 2111, Fax: 86 10 8526 2141  
Chengdu / Tel: 86 28 8675 8111, Fax: 86 28 8675 8141  
Guangzhou / Tel: 86 20 8363 4768, Fax: 86 20 8363 3701  
Shanghai / Tel: 86 21 5868 5111, Fax: 86 21 5866 0969

**FRANCE**  
Tel: 33 1 30 68 89 20, Fax: 33 1 30 68 89 29

**GERMANY**  
Tel: 49 21 59 91 36 0, Fax: 49 21 59 91 3639

**INDIA**  
Tel: 91 80 6782 3200, Fax: 91 80 6782 3232

**SINGAPORE**  
Tel: 65 6484 2388, Fax: 65 6481 6588