

ATEX II 3 G WDG-IV UOP/RP

OXYGEN ANALYZER FOR UOP CCR PLATFORMING PROCESS

ISOLATION VALVE OPTION ALLOWS SENSOR REPLACEMENT WHILE THE PROCESS IS OPERATING

The Process Defined

The UOP CCR Platforming¹ process is widely used in the petrochemical industries to convert paraffins and naphthenes to aromatics with little ring-opening or cracking. A key part of the process is the continuous catalyst regeneration (CCR) in which coke deposits are removed from the catalyst by oxidation. The rate of oxidation must be controlled to prevent thermal damage to the catalyst, and this is achieved through careful control of the oxygen level in the process.

The WDG-IV UOP/RP is the latest in a series of Thermox analyzers, which have been specifically designed to monitor oxygen content in CCR processes since 1980. It uses a nitrogen-operated aspirator to draw a sample of gas from the catalyst regenerator. A portion of this gas passes over the zirconia sensor. Because the aspirator gas contains no oxygen, the sample can simply be returned to the regenerator.

The dual isolation valve option allows the sensor to be replaced without shutting down the CCR process, allowing very high availability to be maintained.

The entire sample stream is heated above the sample dew point, so there is no risk of corrosion. For added protection, an all-Hastelloy sample stream is available as an option.

Benefits include

- ▶ High reliability
- ▶ Hastelloy probe tube
- ▶ 316 SS Wetted parts (Hastelloy C optional)
- ▶ All Wetted parts heated
- ▶ Dual isolation valves (optional)



ATEX WDG-IV UOP/RP

Series 2000 Control Unit

¹CCR Platforming is a registered trademark of Universal Oil Products

SENSOR

Principle of Operation: Close-coupled nitrogen-aspirated oxygen analyzer using zirconium oxide for net oxygen measurement.

Output Range: From 0-1% to 0-100%

Accuracy: $\pm 0.75\%$ of measured value or $\pm 0.05\%$ oxygen, whichever is greater.

Response Time: 90% of a step change <30 seconds

Aspirator Requirements: 4.72 to 9.4 L/min at 0.35 kg/cm² above process pressure

Probe Length/Type:

27" / Hastelloy® C - standard. Other lengths available.

Max. Sample Dewpoint: 200°C

Flow Switch: Integral flow sensor.

Sample Pressure:

Max. 60 psig (413.7 kPa)

Environment:

Ambient Temp.: -20°C to 60°C

Relative Humidity: 10% to 90%, non-condensing

Enclosure: NEMA 4X (IP56) hinged, stainless steel wall mount.

Power Requirements: 115 VAC, $\pm 10\%$, 47-63 Hz, 600 VA max.; 230 VAC, $\pm 10\%$, 47-63 Hz; 1850 VA max.

Calibration Gas Requirements:

Use calibration gases 3.16 kg/cm² or 0.35 kg/cm² above process pressure

O₂ Span Gas: Air

O₂ Zero Gas: 1% O₂, balance N₂

SERIES 2000 CONTROL UNIT

Display: Four-line x 20-character vacuum fluorescent. Displays oxygen, time and date, sample flow, cell temperature, user-programmable text, thermocouple mV or cell mV.

Analog Output: Two isolated linear current outputs. Select O₂, cell temperature, thermocouple mV or cell mV. Hold or track during calibration and select degree of damping. Maximum load 1200 ohms.

Alarms: Two independent oxygen alarms, each high or low selectable. One alarm can be allocated to % oxygen, calibrate or verify. Set relays to energize or de-energize on alarm. Flow alarm. Loss of purge alarm (on Sensor).

Contact Rating: 0.5A, 30V, 10 VA max. noninductive load, AC or DC. SPST type.

Diagnostics: Watchdog timer and service alarms. System test for A/D, RAM, EEPROM and keypad. Flow alarm. Display Line 4 reserved for full text error and diagnostic messages. Twenty-entry event log.

Communications: RS-485, 2-way addressable.

Environment:

Ambient Temp: -10°C to 50°C

Relative Humidity: 0% to 80%, non-condensing

Enclosure: Weatherproof NEMA 4 (IP56). NEMA 4X (IP56) stainless steel available as option.

Calibration: Oxygen cell lifetime extender. Calibrate or verify calibration.

Power Requirements: Nominal 115-230 VAC $\pm 10\%$, 47-63 Hz. max., 75 VA max.

SYSTEM COMPLIANCE:

EMC Compliance: 2004/108/EC

Electronics Safety Compliance: 73/23/EEC

ATEX Directive 94/9/EC

TYPE APPROVAL (LCIE 05 ATEX 6140 X and LCIE 05 ATEX 6140 X / 01)

Series 2000 Control Unit	Ⓔ II 3 G Ex nA IIC T3	-10°C ≤ Ta ≤ 50°C
WDG...	Ⓔ II 3 G Ex nZ IIC T3	-20°C ≤ Ta ≤ 60°C



150 Freeport Road, Pittsburgh, PA 15238
Ph. +1-412-828-9040, Fax +1-412-826-0399
www.ametekpi.com



© 2012, by AMETEK, Inc.
All rights reserved. Printed in the U.S.A.
F-0197 Rev. 4 (0212)

One of a family of innovative process analyzer solutions from AMETEK Process Instruments.
Specifications subject to change without notice.

SALES AND MANUFACTURING:

USA - Delaware
455 Corporate Blvd., Newark DE 19702 • Tel: +1-302-456-4400, Fax: +1-302-456-4444

USA - Oklahoma
2001 N. Indianwood Ave., Broken Arrow OK 74012 • Tel: +1-918-250-7200, Fax: +1-918-459-0165

CANADA - Alberta
2876 Sunridge Way N.E., Calgary, AB T1Y 7H9 • Tel: +1-403-235-8400, Fax: +1-403-248-3550

WORLDWIDE SALES AND SERVICE LOCATIONS:

USA - Texas
Tel: +1-713-466-4900, Fax: +1-713-849-1924

BRAZIL
Tel: 55 19 3825 8770, Fax: 55 19 3935 8773

CHINA
Beijing / Tel: 86 10 8526 2111, Fax: 86 10 8526 2141
Chengdu / Tel: 86 28 8675 8111, Fax: 86 28 8675 8141
Guangzhou / Tel: 86 20 8363 4768, Fax: 86 20 8363 3701
Shanghai / Tel: 86 21 5868 5111, Fax: 86 21 5866 0969

FRANCE
Tel: 33 1 30 68 89 20, Fax: 33 1 30 68 89 29

GERMANY
Tel: 49 21 59 91 36 0, Fax: 49 21 59 91 3639

INDIA
Tel: 91 80 6782 3200, Fax: 91 80 6782 3232

SINGAPORE
Tel: 65 6484 2388, Fax: 65 6481 6588

