

## PRODUCT DATA SHEET

# 120HD Portable Hydrogen Analyzer

Measures the hydrogen concentration in a gas sample, then digitally reports the percent volume of hydrogen in air

The 120HD analyzer functions as a katharometer. It operates by having two parallel tubes, both of which contain gas and heating coils. The gases are examined by comparing the rate of loss of heat from the heating coils into the gas. The coils are arranged in a bridge circuit so that resistance changes due to unequal cooling can be measured.

One channel contains moisture-saturated air and the mixture to be tested is passed through the other channel. Hydrogen has a much higher thermal conductivity than air and so the 120HD is very sensitive to it, but it will also respond to any gas whose thermal conductivity is different from that of air.



### KEY BENEFITS

- Battery-operated and fully portable
- Non-destructive: Sample can be used after analysis
- All wetted surfaces are stainless steel
- Measurement unaffected by changes in ambient temperature or pressure
- Factory-calibrated

### APPLICATIONS

- On ships
- In turbine halls
- During lead-acid battery charging

### KEY MARKETS

- Research and development (R&D)
- Hydrogen in air/steam

PERFORMANCE SPECIFICATIONS

<b>Operating principle</b>	Katharometer
<b>Operating range</b>	0 to 25% H <sub>2</sub> in water-saturated air
<b>Accuracy</b>	±4% full scale (±1% H <sub>2</sub> v/v)
<b>Response time</b>	<1 minute for 90% step change
<b>Repeatability</b>	±2% full scale (±0.5% H <sub>2</sub> v/v)
<b>Environment</b>	Ambient temperature: 10 to 38°C (50 to 100°F)
<b>Relative humidity</b>	0% to 100%
<b>Shock test</b>	MIL-S-901D (Navy) Grade B
<b>Recommended sample gas flow rate</b>	50 ml/min
<b>Sample pressure</b>	5 psi (34 kPa) gauge maximum
<b>Power supply</b>	(1) 6V industrial alkaline lantern battery
<b>Battery life (approximate)</b>	120 hours minimum with backlight
<b>Power drain</b>	210 mA, 6V (with backlight) 170 mA, 6V (without backlight)
<b>Weight</b>	Less than 15 lb with battery

SALES, SERVICE & MANUFACTURING

**USA - Pennsylvania**

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

**USA - Delaware**

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

**Canada - Alberta**

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

**USA**

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

**Brazil**

Tel: +55 19 2107 4100

**France**

Tel: +33 1 30 68 89 20  
Fax: +33 1 30 68 89 99

**Germany**

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

**India**

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

**Singapore**

Tel: +65 6484 2388  
Fax: +65 6481 6588

**China**

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28-8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2018, by AMETEK, Inc. All rights reserved. Printed in the U.S.A. F-0246 Rev 5 (0818)  
One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



To find out more or request a quote visit our website

