

# PRODUCT DATA SHEET

## WDG-V UOP/RP CCR Oxygen Analyzer

Oxygen analyzer for continuous catalytic regeneration (CCR) platforming processes

The UOP CCR Platforming<sup>1</sup> process is widely used in the petrochemical industries to convert paraffins and naphthenes to aromatics with little ring-opening or cracking. A key part of the process is the continuous catalyst regeneration (CCR) in which coke deposits are removed from the catalyst by oxidation. The rate of oxidation must be controlled to prevent thermal damage to the catalyst. This is achieved through careful control of the oxygen level in the process.

### Proven design

The WDG-V UOP/RP is the latest in a series of Thermox analyzers, which have been specifically designed to monitor oxygen content in CCR processes since 1980. It uses a nitrogen-operated aspirator to draw a sample of gas from the catalyst regenerator. A portion of this gas passes over the zirconia sensor. Because the aspirator gas contains no oxygen, the sample can simply be returned to the regenerator.

### Safe servicing

Dual isolation valves allow the sensor to be replaced without shutting down the CCR process, allowing very high availability to be maintained.

### Robust and corrosion-resistant

The entire sample stream is heated above the sample dew point, so there is no risk of corrosion. For added protection, an all-Hastelloy sample stream is available as an option.

(1) CCR Platforming is a registered trademark of Honeywell UOP



## KEY BENEFITS

- Highly reliable design proven for CCR
- Hastelloy probe tube
- Proven integral flow sensor
- 316 SS wetted parts (Hastelloy C optional)
- All wetted parts heated
- Dual isolation valves for serviceability
- Predictive diagnostics and proactive alarms designed for SIL 2

## APPLICATIONS

- Continuous catalytic regeneration (CCR)
- Catalytic reforming/platforming

## KEY MARKETS

- Petrochemical
- Refining

## PERFORMANCE SPECIFICATIONS

## Sensor specifications

<b>Principle of operation</b>	Close-coupled nitrogen-aspirated oxygen (O <sub>2</sub> ) analyzer using zirconium oxide for net O <sub>2</sub> measurement
<b>Output range</b>	From 0-1% to 0-100%
<b>Accuracy</b>	±0.75% of measured value or ±0.05% oxygen, whichever is greater
<b>Response</b>	90% of a process step change < 12 secs
<b>Drift</b>	< 0.1% of cell output per month (< 0.005% O <sub>2</sub> per month with 2% O <sub>2</sub> applied)
<b>Aspirator requirements</b>	Use nitrogen (N <sub>2</sub> ), 10-20 scfh (4.72-9.4 L/min) @ at 0.35 kg/cm <sup>3</sup> above process pressure (or within 15-100 psig or 1.05-7.04 kg/cm <sup>3</sup> )
<b>Analog output</b>	3 isolated linear current outputs for oxygen. Each output can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA and is fully scalable. NAMUR configurable. Hold or track during calibration. Max. load 1200 ohms
<b>Alarms</b>	5 independent, NO alarms. Set relays to energize or de-energize on alarm
<b>Contact rating</b>	0.5A, 30V, 10VA max. non-inductive load, AC or DC
<b>Digital communication</b>	2-wire Modbus RTU, 57.6 KBAud
<b>Configuration</b>	Modbus RTU, AMETEK configuration software, or AMEVision HMI. HART® option available
<b>Diagnostics</b>	Low sample flow, cell and detector age tracking, cell resistance, calibration required, analog current verification
<b>Calibration</b>	Calibrate or verify calibration. Stored calibration and verification data. Selectable calibration gas run time and process recovery time Timed automatic calibration with optional Remote Calibration Unit
<b>Sample pressure</b>	14.69 psig up to 60 psig (101.28 kPa up to 413.7 kPa)
<b>Max sample dew point</b>	200°C (392°F)
<b>Probe type / length</b>	Hastelloy C / 18" (46cm) or 27" (69cm)
<b>Environment</b>	Ambient temperature: -20 to 60°C (-5 to 140°F); Max. Altitude: 2000 meters Relative humidity: 10 to 90%, non-condensing
<b>Enclosure</b>	Hinged IP65
<b>Power requirement</b>	115 VAC, ±10%, 47 to 63 Hz, 740 VA max 230 VAC, ±10%, 47 to 63 Hz, 740 VA max
<b>Calibration gas requirement</b>	Use calibration gases @ 3.0 SCFH (1.4 L/min.) O <sub>2</sub> span gas: O <sub>2</sub> Span Gas: Air or from 1.0 to 100% O <sub>2</sub> , balance N <sub>2</sub> O <sub>2</sub> zero gases: 2% or from 0.1 to 10% O <sub>2</sub> , balance N <sub>2</sub>

## AMEVision HMI specifications

<b>Display</b>	4.2" color 1/4W VGA with graphical user interface. Password-protected
<b>Keypad</b>	18-key membrane
<b>Input</b>	Two-wire Modbus RTU (19200 Baud rate, even parity, 1 stop bit) from analyzer. Host capable of up to eight analyzers
<b>Digital outputs</b>	Two or four-wire Modbus RTU, TCP/IP Ethernet with embedded web server (RJ45 connection), USB port for data collection or software update
<b>Environment</b>	Ambient temperatures from -20 to 55°C (-4 to 131°F)
<b>Power requirements</b>	Nominal 115 to 230 VAC ±10%, 47 to 63 Hz, 75 VA max
<b>Enclosure</b>	IP65 (NEMA 4X)
<b>System compliance</b>	EMC Directive 2004/108/EC; Low Voltage Directive 73/23/EEC. Two hazardous area configurations: NEC/CEC Class 1, Div 2 and ATEX Zone 2

## SALES, SERVICE &amp; MANUFACTURING

## USA - Pennsylvania

150 Freeport Road  
Pittsburgh PA 15238  
Tel: +1 412 828 9040  
Fax: +1 412 826 0399

## USA - Delaware

455 Corporate Blvd.  
Newark DE 19702  
Tel: +1 302 456 4400  
Fax: +1 302 456 4444

## Canada - Alberta

2876 Sunridge Way NE  
Calgary AB T1Y 7H9  
Tel: +1 403 235 8400  
Fax: +1 403 248 3550

## WORLDWIDE SALES AND SERVICE LOCATIONS

## USA

Tel: +1 713 466 4900  
Fax: +1 713 849 1924

## Brazil

Tel: +55 19 2107 4100

## France

Tel: +33 1 30 68 89 20  
Fax: +33 1 30 68 89 99

## Germany

Tel: +49 2159 9136 0  
Fax: +49 2159 9136 39

## India

Tel: +91 80 6782 3200  
Fax: +91 80 6780 3232

## Singapore

Tel: +65 6484 2388  
Fax: +65 6481 6588

## China

Beijing  
Tel: +86 10 8526 2111  
Fax: +86 10 8526 2141  
Chengdu  
Tel: +86 28 8675 8111  
Fax: +86 28 8675 8141  
Shanghai  
Tel: +86 21 5868 5111  
Fax: +86 21 5866 0969



© 2019, by AMETEK, Inc. All rights reserved. Printed in the PI0010 (1119).

One of a family of innovative process analyzer solutions from AMETEK Process Instruments.  
Specifications subject to change without notice.

